## BENTLEY

Balustrade (BBALUO)

| Product Code:                   | BBALU00136V                             |
|---------------------------------|---|
| Style Number:                   | BBALU0136V802116057                     |
| Backing & Size:                 | LVT 5 mm 18x36                          |
| Wear Layer Thickness:           | 20 mil                                  |
| Install Type:                   | Direct Glue                             |
| Maintenance:                    | Inherent No Wax Surface                 |
| Pieces per Carton:              | 6                                       |
| Coverage per Carton:            | 27 ft² (2.51 m²)                        |
| Weight per Carton:              | 48.8 lbs (22.1 kg)                      |
| Classification:                 | ASTM F1700, Class III Type B            |
| Dimensional Stability:          | Pass - ≤ 0.02 in, ASTM F2199            |
| Flexibility:                    | Pass - no cracks or breaks, ASTM F137   |
| Resistance to Heat:             | Pass - ΔE ≤ 8, ASTM F1514               |
| Resistance to Light:            | Pass - ΔE ≤ 8, ASTM F1515               |
| Resistance to Chemicals:        | Pass - slight change max, ASTM F925     |
| Static Load Recovery:           | Pass - 1750 psi, ASTM F970 modified     |
| Static Coefficient of Friction: | Pass - ≥ 0.50, ASTM D2047               |
| Critical Radiant Flux:          | Pass - Class 1, ≥ 0.45 W/cm², ASTM E648 |
| Sound Transmission Class:       | STC - 62, ASTM E90                      |
| Impact Insulation Class:        | IIC - 52, ASTM E492                     |
| Indoor Air Quality:             | FloorScore™ Certified                   |
| Adhesive:                       | Bentley Healthbond 2399                 |
|                                 |   |

## Installation Methods





Ashlar

Herringbone

Installation: All Bentley Luxury Vinyl Tile products must be installed by flooring installers who are professionally trained and experienced in current techniques and industry accepted standards for professional installation of luxury vinyl tile flooring. Please refer to the current issue of Bentley's Luxury Vinyl Tile (LVT) Installation Guidelines.

Adhesives: All Bentley Luxury Vinyl Tile products must be installed with adhesives purchased through Bentley, and matched to requirements of Bentley for flooring material, site and project conditions. Please refer to the current issue of Bentley's Luxury Vinyl Tile (LVT) Installation Guidelines.

Maintenance: Please refer to the current issue of Bentley's Luxury Vinyl Tile (LVT) Maintenance Guideline.

Warranty: 15 Year Limited. Product warranted in accordance with the terms and conditions of Bentley's standard printed warranty in effect at time product is sold. All other warranties, including without limitation any implied warranties of merchantability or fitness for a particular purpose are hereby disclaimed. For complete warranty information, please refer to Bentley's Luxury Vinyl Tile (LVT) Warranty Terms. ©2024 Bentley Mills, Inc.

Need additional samples or information? 800.423.4709 | BENTLEYMILLS.COM/LVT